

37/7/6 (Item 6 from file: 347)  
DIALOG(R)File 347:JAPIO  
(c) 2006 JPO & JAPIO. All rts. reserv.

03820556

PREPARATION OF EXPANDED CROSSLINKED POLYOLEFIN MOLDING

PUB. NO.: 04-185656 [\*JP 4185656\* A]  
PUBLISHED: July 02, 1992 (19920702)  
INVENTOR(s): MIYATA HIROYUKI  
TAKAHASHI SUSUMU  
NIWA TOSHIO  
APPLICANT(s): FUJIKURA LTD [000518] (A Japanese Company or Corporation), JP  
(Japan)  
APPL. NO.: 02-317458 [JP 90317458]  
FILED: November 21, 1990 (19901121)

ABSTRACT

PURPOSE: To obtain the title molding with inexpensive simple equipment at good efficiency within a short time by irradiating a molding comprising a crystalline polyolefin and a blowing agent with ultraviolet rays under specified temperature conditions.

CONSTITUTION: A crystalline polyolefin (e.g. polyethylene) is mixed with a blowing agent (e.g. azodicarbonamide) and optionally a blowing assistant (e.g. urea), a photosensitizer (e.g. benzophenone), a crosslinking assistant (e.g. triallyl cyanurate), and the obtained mixture is molded into any desired shape. This molding is irradiated with ultraviolet rays under the conditions of a temperature from the crystalline melting temperature of the polyolefin to its decomposition temperature to obtain a expanded crosslinked polyolefin molding. In this way, even a polyolefin molding of a relatively large wall thickness can be simultaneously subjected to crosslinking and foaming within a short time.

009145467/7

DIALOG(R)File 351:Derwent WPI  
(c) 2006 Thomson Derwent. All rts. reserv.

009145467

WPI Acc No: 1992-272906/199233

Crosslinked polyolefin foam mouldings prepn. by UV irradiation -  
comprising UV irradiating moulding consisting of crystalline polyolefin  
e.g. LDPE, foaming agent, photosensitiser and crosslinker

Patent Assignee: FUJIKURA LTD (FUJD )

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 4185656	A	19920702	JP 90317458	A	19901121	199233 B

Priority Applications (No Type Date): JP 90317458 A 19901121

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
JP 4185656	A		5 C08J-009/06	

Abstract (Basic): JP 4185656 A

Prepn. of crosslinked polyolefin foam mouldings comprises U.V.

irradiating a moulding consisting of crystalline polyolefin, foaming agent and, opt. a assistant foaming agent and, opt. photo-sensitiser, and assistant crosslinking agent at temp. more than the m.pt. of the crystal of the crystalline polyolefin and less than the decomposition temp. of the foaming agent.

The mouldings are used for coating of electric wire and electric cable. The mouldings are cylindrical prods, e.g. tube, pipe, etc. The mouldings are flat boards, e.g. film, sheet, etc.

USE/ADVANTAGE - The prepn. can generate high level of crosslinking and foaming at the same time to comparatively thick walled polyolefin mouldings in a short time. In an example, the crystalline polyolefin is e.g. low density polyethylene, high density polyethylene, linear polyethylene, ultra-low density polyethylene, ultra high molecular polyethylene, etc. which have high crosslinking efficien

Dwg.O/O

Derwent Class: A17; A32; A85; X12

International Patent Class (Main): C08J-009/06

International Patent Class (Additional): C08J-003/28; C08L-023-02;  
H01B-003/44; H01B-013/14